Certificate Number: 11-HS824251-PDA 12/FEB/2016



Confirmation of Product Type Approval

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This certificate reflects the information on the product in the ABS Records as of the date and time the certificate is printed.

Pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 11/DEC/2018. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until 09/NOV/2016 subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Product Name: Expansion Joint, Bellows Type Model Name(s): 520385-A

Presented to:

HOSE MASTER, LLC 1233 EAST 222ND STREET United States

Intended Service: Marine and Offshore Applications.

Description: Expansion Joint type Universal of 16" x 38.5" with 4 plies constructed with

A-240-316/316L, flanges class 300 16", pipe seamless sched. 30 of 16" and liner of

14.5" diameter with 0.062" of thickness.

Tier: 3

Ratings: Design Pressure: 600 PSI (41.37 BAR) Design Temperature: 500 °F (260 °C)

Design Cycle Life: 10000

Service Restrictions: Unit Certification is not required for this product. If the manufacturer or purchaser

request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be

clearly defined.

Comments: i) Bellows design for 15 psi and greater will hold Full Vacuum. ii) Hydrostest to 900

Psi at Ambient Temperature.

Notes / Documentation: Supporting Documentation: Dwg No. 520385 Rev. A 16 x 38.5" OAL UNIVERSAL

EXPANSION JOINT: Bellows Design Analysis Expansion Joint 520385-A dated 27

October 2011.

Term of Validity: This Product Design Assessment (PDA) Certificate 11-HS824251-PDA, dated

10/Nov/2011 remains valid until 09/Nov/2016 or until the Rules or specifications used in the assessment are revised (whichever occurs first). This PDA is intended

Certificate Number: 11-HS824251-PDA

for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

ABS Rules: 2011 Steel Vessles Rules 1-1-4/7.7, 1-1-Appendix 3, 4-6-2/5.8.2

National Standards: International Standards: Government Authority:

EUMED:

Others: None

 Model Certificate
 Model Certificate No
 Issue Date
 Expiry Date

 PDA
 11-HS824251-PDA
 10/NOV/2011
 09/NOV/2016

ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.