

CERTIFICATE OF COMPLIANCE

Certificate Number 20190724-MH17129
Report Reference MH17129-19920304
Issue Date 2019-JULY-24

Issued to: HOSE MASTER L L C
1233 E 222ND ST, CLEVELAND OH 44117

This certificate confirms that representative samples of FLEXIBLE CONNECTORS FOR FLAMMABLE LIQUIDS
See addendum page


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: CAN/ULC-S633, Standard For Flexible Connector Piping For Fuels
Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number 20190724-MH17129
Report Reference MH17129-19920304
Issue Date 2019-JULY-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL – Flexible Connectors designated “Fire-Shield”, Model Nos. FSMM 0.75, 1.0, 1.5, 2.0, 3.0; FSMU 3.0; FSMF 1.5, 2.0; FSUU 3.0; FSFF 1.5, 2.0; FSM2M 1.5; FSMS 1.5, 2.0; FSMSE 1.5, 2.0; FSFS 1.5, 2.0; FSFSE 2.0; FSMW 1.5, 2.0; FSSW 1.5, 2.0; FSS2W 1.5; FSSME 1.5, 2.0; FSSFE 1.5, 2.0; FSSSE 1.5, 2.0; FSSWE 1.5, 2.0; FSS2M 1.5; FSW2M 1.5; FSWWE 1.5; 2.0; FSWSE 1.5, 2.0; FSS2WE 1.5; FSSE2WE 1.5; FSTMM2 1.5; FSQ2M 1.5; FSQF 1.5, 2.0; FSQM 1.5, 2.0, 3.0; FSQQ 1.5, 2.0, 3.0; FSQSE 1.5, 2.0; FSQWE 1.5, 2.0; FSQT 1.5, 2.0. Model numbers may have a suffix correlating to the connector length.

CNL – Flexible Connectors designated “Fire-Shield”, Model Nos. FSMM 0.75, 1.0, 1.5, 2.0, 3.0; FSMU 3.0; FSMF 1.5, 2.0; FSUU 3.0; FSFF 1.5, 2.0; FSM2M 1.5; FSMS 1.5, 2.0; FSMSE 1.5, 2.0; FSFS 1.5, 2.0; FSFSE 2.0; FSMW 1.5, 2.0; FSSW 1.5, 2.0; FSS2W 1.5; FSSME 1.5, 2.0; FSSFE 1.5, 2.0; FSSSE 1.5, 2.0; FSSWE 1.5, 2.0; FSS2M 1.5; FSW2M 1.5; FSWWE 1.5; 2.0; FSWSE 1.5, 2.0; FSS2WE 1.5; FSSE2WE 1.5; FSTMM2 1.5; FSQ2M 1.5; FSQF 1.5, 2.0; FSQM 1.5, 2.0, 3.0; FSQQ 1.5, 2.0, 3.0; FSQSE 1.5, 2.0; FSQWE 1.5, 2.0; FSQT 1.5, 2.0. Model numbers may have a suffix correlating to the connector length.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

