

CERTIFICATE OF COMPLIANCE

Certificate Number 20170116-MH27191
Report Reference MH27191-20081106
Issue Date 2017-JANUARY-16

Issued to: HOSE MASTER L L C
1233 E 222Nd St
Cleveland OH 44117-1104

**This is to certify that
representative samples of**

FLEXIBLE METAL HOSE CERTIFIED FOR CANADA
See Addendum Page For models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

standard used to investigate products in this category is
ULC/ORD-C536, "Flexible Metallic Hose."

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20170116-MH27191
Report Reference MH27191-20081106
Issue Date 2017-JANUARY-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models/Product

All metallic flexible hose type pipe connector in the following models, sizes and their respective maximum rated working pressure.

<u>Model</u>	<u>End Fittings (NPT)</u>	<u>Nominal ID</u> <u>mm (in.)</u>	<u>Maximum Rated</u> <u>Working Pressure</u>	
			<u>kPa</u>	<u>psi</u>
FSMM 0.75	0.75M x 0.75M	19 (3/4)	1034	150
FSMM 1.0	1 M x 1 M	25 (1)	1034	150
FSMM 1.5	1-1/2 M x 1-1/2 M	38 (1-1/2)	1034	150
FSMF 1.5	1-1/2 M x 2 F	38 (1-1/2)	1034	150
FSMS 1.5	1-1/2 M x 1-1/2 M Swivel	38 (1-1/2)	345	50
FSFS 1.5	1-1/2 F x 1-1/2 M Swivel	38 (1-1/2)	345	50
FSMM 2.0	2 M x 2 M	50 (2)	1034	150
FSMF 2.0	2 M x 2 F	50 (2)	1034	150
FSMS 2.0	2 M x 2 M Swivel	50 (2)	345	50
FSFS 2.0	2 F x 2 M Swivel	50 (2)	345	50
FSMM 3.0	3 M x 3 M	75 (3)	1034	150

The overall length does not exceed 2400 mm (8 ft.)



Bruce Mahrenholz, Director North American Certification Program
 UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>