

CERTIFICATE NUMBER EFFECTIVE DATE EXPIRY DATE ABS TECHNICAL OFFICE 20-2056472-PDA-DUP 30-Nov-2020 29-Nov-2025 Houston ESD - Piping

CERTIFICATE OF

Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

HOSE MASTER, LLC.

located at

12101 MCLAIN BLVD., HOUSTON, TX, United States, 77071

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product Flexible Metal Hose Assemblies

Model Annuflex, Masterflex, Pressuremax, ChemKing

This Product Design Assessment (PDA) Certificate remains valid until 29/Nov/2025 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Gongin Lee
Yongjin Lee, Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

HOSE MASTER

12101 MCLAIN BLVD.

HOUSTON TX

United States 77071

Telephone: 216-6481-2020

Fax: 216-6481-7557

Email: websales@hosemaster.com Web: www.hosemaster.com

Tier: 3 - Type Approved, unit certification not required

Product: Flexible Metal Hose Assemblies

Model: Annuflex, Masterflex, Pressuremax, ChemKing

Intended Service:

Marine and Offshore Applications

Especially, Annuflex 4, 6, 8, 8 & 10 T304 Double Braided T316L Corrugated Hoses (Models: AF57550400, AF57550600, AF57550800 & AF57551000) also for LNG cargo.

Description:

Flexible Metal Hose Assemblies.

See the attached document for Annuflex, MasterFlex, PressureMax & ChemKing Hose Maximum Pressure Ratings, Size, etc.

Annuflex 4", 6", 8" & 10" T304 Double Braided T316L Corrugated Hoses (Models: AF57550400, AF57550600, AF57550800 & AF57551000) also for LNG cargo: -165 deg. Č to 50 deg. C up to 150 psi

Service Restriction:

- 1-1) Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.
- 1-2) With regard to Annuflex 8" T304 Double Braided T316L Corrugated Hose (Model: AF57550800) for cryogenic services, each new length of cargo hose produced shall be hydrostatically tested at ambient temperature to a pressure not less than 1.5 times its specified maximum working pressure, but not more than two fifths of its bursting pressure. The hose shall be stencilled, or otherwise marked, with the date of testing, its specified maximum working pressure and, if used in services other than ambient temperature services, its maximum and minimum service temperature, as applicable per 5C-8-5/11.7.3 of MVR.
- 2) The hoses are to be complete with factory assembled end fittings or factory supplied ends made of steel only and installed in accordance with manufacturer's procedures.
- 3) The type of end connections utilized (e.g. threaded, flanged, etc.) are to comply with the applicable requirements and limitations in the Rules.
- 4) Hose assemblies are to be installed only when flexibility is required and are not to be subject to torsional deflection under normal conditions. In addition, the length of the hose is to be limited to that required for flexibility only.

Comments:

- 1) The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.
- 2) Flexible hoses are to be permanently marked by the manufacturer with the following details per MVR 4-6-2/5.7.6: Hose manufacturer's name or trademark, Date of manufacture (month/year), Designation type reference, Nominal diameter, Pressure rating and Temperature rating

Notes/Drawing/Documentation:

Annuflex Catalog Sheets, Rev. 2

Chemking Catalog Sheets, Rev. 2

Fittings Catalog Sheets,

Masterflex Catalog Sheets;

Pressuremax Catalog Sheets

Burst and Deformation Testing dated 5 November 2008;

Assembly Prep for Testing dated 27 May 2005;

Recording and Generating Pressure Test Analysis Results dated 19 December 2006;

Analysis of Burst Deformation Chart dated 27 May 2005;

Pulse Test Report for Annuflex 8" hose by Hose Master dated 23 July 2019;
Pulse Test Report for Annuflex 4", 6" & 10" by Hose Master dated 29 October 2020;
ABS Cryogenic prototype test report for Annuflex 8" dated 02 August 2019;

ABS Burst Test Report for Annuflex 8" at Upper Temperature Limit dated 17 October 2019;

HOSE MASTER

12101 MCLAIN BLVD.

HOUSTON TX

United States 77071

Telephone: 216-6481-2020

Fax: 216-6481-7557

Email: websales@hosemaster.com

Web: www.hosemaster.com

Tier: 3 - Type Approved, unit certification not required

ABS Cryogenic and burst prototype test report for Annuflex 4", 6" & 10" dated 14 August 2020;

Burst Test Report 1906-221N at Lower Temperature Limit by Keystone Compliance for Annuflex 8", Rev. B dated 25 June 2019:

Burst Test Report 1906-247NB at Lower Temperature Limit by Keystone Compliance for Annuflex 4", 6" & 10", Rev. A dated 10 August 2020

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 29/Nov/2025 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

The Rules for Conditions of Classification, 2020 Marine Vessels Rules:1-1-4/7.7, 1-1-A3, 1-1-A4, which covers the followings;

2020 Rules for Building and Classing Marine Vessels:4-6-2/5.7 and 5C-8-5/11.7;

The Rules for Conditions of Classification - Offshore Units and Structures, 2020 Mobile Offshore Units Rules: 1-1-4/9.7, 1-1-A2, 1-1-A3 which covers the following:

2020 Rules for Building and Classing Mobile Offshore Units: 4-2-1/11.29;

National:

NA

International:

NA

Government:

NA

EUMED:

NA

OTHERS:

NA